

HEPA Filters

AstroCel® III

Product Overview

- Ideal for demanding operating conditions in critical applications
- Longer service life
- Low energy consumption and lower resistance to airflow



Specification

EN1822	H13, H14
Filter Depth (mm)	292
Media Type	Fibreglass
Frame Material (Standard)	Galvanised Steel
Frame Material (Optional)	Stainless Steel, Aluminium
Gasket Material (Standard)	PU
Gasket Material (Optional)	Neoprene, EPDM
Gasket Position (Standard)	Downstream
Gasket Position (Optional)	Both Sides, Upstream
Special Size Available	No
Antimicrobial Available	No
Header Type	None Header
Recommended Final Resistance	750 Pa
Max Operating Temperature	70°C

Product Information

Part Number	Actual Size mm (H x W x D)	Rated Airflow (CMH)	Rated Initial Resistance (Pa)
<b>H13</b>			
M370-206-004	610 x 305 x 292	1,275	250
M570-206-004	610 x 305 x 292	1,500	
M370-206-005	610 x 610 x 292	3,400	
M570-206-005	610 x 610 x 292	4,000	
<b>H14</b>			
M371-206-004	610 x 305 x 292	1,200	250
M571-206-004	610 x 305 x 292	1,400	
M371-206-005	610 x 610 x 292	3,000	
M571-206-005	610 x 610 x 292	3,500	

AAF has a policy of continuous product research and improvement and reserves the right to change design and specifications without notice.

www.aafintl.com

